

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

1 Identification

- **Product identifier** 325B4
- **Trade name:** 325B4 4P Metered IMPACT GENAIRE Ocean Breeze
- **Manufacturer article number:** EAEDC265
- **Application of the substance / the mixture** Air Freshener
- **Details of the supplier of the safety data sheet** (740)(3)
- **Manufacturer/Supplier:**
Impact Products, LLC
2840 Centennial Road
Toledo, Ohio 43617-1898
- **Information department:** Product Safety Department
- **Emergency telephone number:**
Phone: 800.333.1541
Fax: 800.333.1541
Email: custserv@impact-products.com
Emergency Telephone 24 hr
INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Aerosol 1 H222 Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS04



GHS07

- **Signal word** Danger

- **Hazard-determining components of labeling:**

acetone

2-(4-tert-Butylbenzyl)propionaldehyde

α-hexylcinnamaldehyde

- **Hazard statements**

Extremely flammable aerosol.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 1)

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 1

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 4

Reactivity = 1

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	50-100%
75-28-5	isobutane	10-25%
74-98-6	propane	2.5-<10%
106-97-8	butane	0.1-≤2.5%
	Fragrance Trade Secret (740)	0.1-≤2.5%

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

80-54-6 2-(4-tert-Butylbenzyl)propionaldehyde

(Contd. of page 2)

0.1-<1%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
Use fire-extinguishing media appropriate for surrounding materials. Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

67-64-1	acetone	200 ppm
75-28-5	isobutane	5500* ppm
74-98-6	propane	5500* ppm
106-97-8	butane	5500* ppm
110-91-8	morpholine	30 ppm
142-90-5	dodecyl methacrylate	6.9 ppm
100-51-6	Benzyl alcohol	30 ppm

· PAC-2:

67-64-1	acetone	3200* ppm
75-28-5	isobutane	17000** ppm
74-98-6	propane	17000** ppm
106-97-8	butane	17000** ppm

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

		(Contd. of page 3)
110-91-8	morpholine	1,300 ppm
142-90-5	dodecyl methacrylate	76 ppm
100-51-6	Benzyl alcohol	52 ppm
· PAC-3:		
67-64-1	acetone	5700* ppm
75-28-5	isobutane	53000*** ppm
74-98-6	propane	33000*** ppm
106-97-8	butane	53000*** ppm
110-91-8	morpholine	8000** ppm
142-90-5	dodecyl methacrylate	460 ppm
100-51-6	Benzyl alcohol	740 ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Do not spray on a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

67-64-1 acetone	
PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
	BEI
75-28-5 isobutane	
TLV	Short-term value: (2370) mg/m ³ , (1000) ppm
	NIC-EX
74-98-6 propane	
PEL	Long-term value: 1800 mg/m ³ , 1000 ppm
REL	Long-term value: 1800 mg/m ³ , 1000 ppm
TLV	refer to Appendix F in TLVs&BEIs book; NIC-EX

(Contd. on page 5)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 4)

106-97-8 butane

REL	Long-term value: 1900 mg/m ³ , 800 ppm
TLV	Short-term value: (2370) mg/m ³ , (1000) ppm
	NIC-EX

· **Ingredients with biological limit values:****67-64-1 acetone**

BEI	50 mg/L
	Medium: urine
	Time: end of shift
	Parameter: Acetone (nonspecific)

· **Additional information:** The lists that were valid during the creation were used as basis.· **Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:** Not required.· **Protection of hands:**

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Safety glasses



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Aerosol
Color:	According to product specification
Odor:	Characteristic

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 5)

· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-11 °C (12 °F)
· Flash point:	< 0 °C (< 32 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	460 °C (860 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.8 Vol %
Upper:	13.0 Vol %
· Vapor pressure at 20 °C (68 °F):	3000 hPa (2250 mm Hg)
· Density:	Not determined.
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	83.8 %
VOC content:	26.1 %
	260.5 g/l / 2.17 lb/gl
Solids content:	4.2 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 6)

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** Irritating effect.

- **Sensitization:** Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

110-91-8 morpholine

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, IMDG, IATA** UN1950

- **UN proper shipping name**

- **DOT** Aerosols, flammable

- **IMDG** AEROSOLS

- **IATA** AEROSOLS, flammable

(Contd. on page 8)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 7)

· **Transport hazard class(es)**· **DOT**

· **Class** 2.1
 · **Label** 2.1

· **IMDG, IATA**

· **Class** 2.1
 · **Label** 2.1

· **Packing group**· **DOT, IMDG, IATA** not regulated· **Environmental hazards:**· **Marine pollutant:** No· **Special precautions for user**

Warning: Gases

· **Danger code (Kemler):**

-

· **EMS Number:**

F-D,S-U

· **Stowage Code**

SW1 Protected from sources of heat.

· **Segregation Code**

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 75 kg

On cargo aircraft only: 150 kg

· **IMDG**· **Limited quantities (LQ)**

1L

· **Excepted quantities (EQ)**

Code: E0

Not permitted as Excepted Quantity

· **UN "Model Regulation":**

UN 1950 AEROSOLS, 2.1

US

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 8)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
75-28-5	isobutane
74-98-6	propane
106-97-8	butane
25265-71-8	oxydipropanol
80-54-6	2-(4-tert-Butylbenzyl)propionaldehyde
118-58-1	benzyl salicylate
101-86-0	α -hexylcinnamaldehyde
110-91-8	morpholine
142-90-5	dodecyl methacrylate
78-70-6	Linalool
106-22-9	Citronellol
127-51-5	Iraldeine gamma
106-24-1	Geraniol
5392-40-5	Citral
100-51-6	Benzyl alcohol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
---------	---------	---

· TLV (Threshold Limit Value established by ACGIH)

67-64-1	acetone	A4
110-91-8	morpholine	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 9)

· **Hazard pictograms**



GHS02 GHS04 GHS07

· **Signal word** Danger

· **Hazard-determining components of labeling:**

acetone

2-(4-tert-Butylbenzyl)propionaldehyde

 α -hexylcinnamaldehyde

· **Hazard statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not pierce or burn, even after use.

Do not spray on an open flame or other ignition source.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wear protective gloves / eye protection / face protection.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Specific treatment (see on this label).

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER/doctor if you feel unwell.

Wash contaminated clothing before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

Store locked up.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product Safety Department

· **Contact:** 800.333.1541

· **Date of preparation / last revision** 08/17/2017 / 9

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 11)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 08/17/2017

Reviewed on 08/17/2017

Trade name: 325B4 4P Metered IMPACT GENAIRE Ocean Breeze

(Contd. of page 10)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Aerosol 1: Aerosols – Category 1

Press. Gas: Gases under pressure – Compressed gas

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

· **Sources**

Additional Information Section 11 and Section 15

“According to IARC Morpholine is not classifiable as to its carcinogenicity to humans (Group 3).

IARC (1989) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Vol. 47, Some Organic Solvents, Resin Monomers and Related Compounds, Pigments and Occupational Exposures in Paint Manufacture and Painting, Lyon, pp. 199–213”

· *** Data compared to the previous version altered.**

US